



AGRHIPAC is a LLDPE Cast coextruded stretch film, especially designed for agricultural applications to wrap bales. It is suitable for ensiling forage for farm animals and for wrapping all types of round and square bales in different environmental conditions.

Characteristic	Method	Unit	Direction	S010 - 25 µm	Tolerances
Impact resistance	ASTM D1709 A	g	-	200	10%
Tensile strength at break	ASTM D882 B	MPa	Machine Direction	25.2	10%
			Transversal Direction	22.8	10%
Tensile strength at yield	ASTM D882 B	MPa	Machine Direction	11.5	10%
			Transversal Direction	8.3	10%
Elongation at break	ASTM D882 B	%	Machine Direction	450	10%
			Transversal Direction	700	10%
Tear Resistance	ASTM D1922	mN	Machine Direction	2438	10%
			Transversal Direction	7024	10%
Cling* (@70% elongation)	Internal	g/m	-	220	10%

* This value has been measured on Laboratory Test Machine and it refers to the dimension of the film width (g/1meter film width)

Stretch GARANTED	AUV 12 months GARANTED	Coloured**	Net Roll (coreless)
70%		GREEN/WHITE/BLACK	

HIPAC STRETCH FILM HAS BEEN
DESIGNED TO BE 100% RECYCLABLE



** Other colours are available on customer's request

The above values are to be considered as indicative in order to facilitate the choice and usage, but are not given for guarantee purposes. Hipac Group reserves the right to modify them, if necessary, without previous notice. Products in conformity with our Technical Specification. The present document is property of Hipac S.p.A. It cannot be copied, published or redistributed without prior written consent of Hipac S.p.A.